



GE Water & Process Technologies

Tonkaflo Pump Model AS40409KTE

[CUTSHEET](#)
[CURVE](#)
[DRAWING](#)
[CAD SYMBOLS](#)
[OPTIONS](#)
[SUMMARY](#)

Operation at 90.84 m3/hr

Head Boost **172.5 meters**
 Efficiency **78%**
 NPSH **10 meters**
 Brake **55 kW**

Motor

HP **75.0**
 RPM **3450**
 Enclosure **TEFC**
 Voltage **230/460 VAC**
 Frequency **60**
 Phase **3**

Material

Inlet Housing **316SS**
 Discharge Housing **316SS**
 Shell **304SS**
 Shaft **304SS**
 Stages **304SS**
 Mech Seal Elast **EPDM**
 Shell/Seal O-rings **EPDM**
 Int Stage Seals **Teflon***
 Shaft Bearings **Teflon***

Flow Range

Minimum **51.1 m3/hr**
 Maximum **119.23 m3/hr**

Bedplate

N/A

Connections

Inlet **4 inch Victaulic**
 Discharge **4 inch Victaulic**

Seals

Arrangement **Standard**
 Max Inlet Pres **14 bar**
 Max Dis Pres **52 bar**

Shipping

Weight **703 kgs.**
 Dimensions **292 x 99 x 89 cm.**
 (L x W x H)

Stages

Stages **9**

Description	Part Number	List Price (USD)
AS40409KTE-Pump Close-Coupled to 75 Hp, 3-phase, TEFC, 364/365TSC, 1.15SF	1225631	\$18,840.00
		TOTAL: \$18,840.00

Prices are suggested retail price and are subject to change without notice.

*Viton and Teflon are trademarks of E.I. DuPont de Nemours and Company, Inc.

Copyright General Electric Company 1997-2010